



## **TECHNICAL DATA SHEET**

### *Extrema Edilizia*

#### **Product Description**

This Acrylic is a one component, plastic elastic sealant based on an acrylic emulsion. The product is almost odour free and is not corrosive towards metal.

After application the product forms a tough plastic elastic rubber by evaporation of water from the sealant.

#### **Applications**

Joints in the building industry between wooden and metal window frames and concrete and brickwork. Joints between stairs and walls, between concrete and ceiling elements, between wall and ceiling, skirting boards and windowsills.

For inside applications.

In general Acrylic will show good adhesion without a primer on building materials like concrete, brickwork, painted wood, anodised aluminium and uPVC

#### **Limitations**

Among others not recommended for continuous water immersion and not for PE, PP, Teflon and bituminous surfaces.

Painting over with highly filled emulsion paints can cause cracks in the paint film.

#### **Surface preparation and finishing**

Surfaces must be clean, dry and sound.

Use diluted Acrylic as a primer for highly porous surfaces. Finish with white spirit.

#### **Available colours**

White, grey, brown and black

#### **Safety**

Safety data sheet are available upon request.

#### **Warranty**

The producer of the raw material warrants that its product complies, within its shelf life, to its specification. The liability shall in no case exceed the amount fixed in our Conditions of Sale.

In no event the producer of the raw material is liable for any incidental or consequential damage.

#### **Liability**

All supplied information is the result of our tests and experience and is of general nature.

However, they do not imply any liability. It is the responsibility of the user to verify by his own tests if the product is suitable for the application.

*General*

		<b>Dimension</b>	
Basis			acryl emulsion
Application temperature		°C	+5 / +40
Application rate	3mm / 6,3 bar	g/min	1500
Flow	ISO 7390	mm	<2
Density		g/ml	1,56
Skin over time	23°C / 55% RF	min	5
Frost resistant till -15°C during transport			non
Shelf life between +5°C and +25°C		Month	12
Paintable			